IKEA Package Test Application Form

QF 701-2N

Applicant Information	Supplier No: Supp		lier Name:				
	Supplier Address:						
	Supplier Contact:			Phone/Mobile:		E-mail:	
	IKEA Contact:			E-mail:			
	Invoice	Invoice Title:					
Invoice Information	Invoice delivery address:						
	Invoice	Invoice Contact:			e:	E-mail:	
	VAT no	VAT no:					
Service required: Regular Express							
Product Testing Types: Verifying Test* Prototype Test *By signing Verifying test, the supplier accepts that the results and the test report are shared with concerned co-workers at Inter IKEA.							
Sample Information (Items with * are very important. Without *Paper Composition; *Batch number / Product date, you run the risk that TR not complying with all IKEA requirements for the required information)							
Article							
Article No. :		Article N		ame Dat		te Stamp/Production Date:	
⊠Raw Material							
Basic informa	tion:	on: *Material Producer: * Batch Number / Production Dat			Material Description:		
Communicated Pa			ction Date:		Sample Amount:		
Corrugated Bo	oaru:				*CB Colour: Brown/Brown, White/Brown, White/White		
		*Flute Type:E,B,C,A,BA,BC,AC,Other:					
Dames Ballet F		*Paper Composition (Type & Weight for each layers) (e.g.: A160g/F120g/B120g):					
Paper Pallet-F	-eet:	. 661 61261			· 		
Paper Pallet-L	Load	*Feet Filler Quality (e.g.:CB25): d			*Feet Tray Quality(e.g.:CB10):		
Bearer:		*Load Bearer Code: LE	305, <u> </u>	LB10,	LB10, *Load Bearer Quality (e.g.:CB150/CB230):		
Description of Corner mat for Penetration test:		□LB20, □LB30 □LB4	10, 🔲			CD130/CD230).	
Additional Information							
Date: Authorized signature & Company chop:							
Test Item(s) Required (Please tick) and sample requirement:							
Packaging general requirements, IOS-P-0010:							
Complete test Corrugated board (25pcs, 50*50cm) Paper pallet							
Flat crush test (FCT) ISO 3035 (3pcs, 50*50cm) Edgewise crush test (ECT) ISO 3037 (3pcs, 50*50cm)					Compress	ion test for feet (15pcs feet)	
Thickness ISO 3034 (2pcs, 50*50cm)					Weight of	the feet	
Bursting strength test (BST) ISO 2759 (5pcs, 50*50cm)					Complete test Load I	Bearer	
☐Bending stiffness ISO 5628 (8pcs, 50*50cm) ☐Cobb60 test ISO 535 (4pcs, 50*50cm) a						deflection test (10pcs on MD, 45*10cm	
Nominal Weight (g/m²) (2pcs, 50*50cm)					and 10pcs on CD direction, 45*10cm) Cobb60 test (15pcs, 14*14cm)		
Flute type					Thickness		
Dry Weight (4pcs, 50*50cm)					Corner penetration test (15 pcs 10cm length)		
Mottling Coefficient (STFI Method) - only for white CB (3pcs, 20*20cm) It is recommended to send of white top liners i.g.							

Sample Submittal Guide: 1. The specimen should be provided with identification (e.g.: CB/LB/IF code) in one corner and be as small as practicable. 2. Each specimen shall be kept flat, free from wrinkles and folds, and before converting process to boxes or pallets.